



CB Series - CB

LED Replacement Corn Bulb

2,600 - 13,000 Lumens

Project:

Location:

Cat.No:

Notes:

Product Description

The CB Series replacement bulbs deliver a cost-effective LED lighting solution perfect for various general-use applications. Specifically engineered to replace outdated fluorescent lamps, these bulbs provide a powerful upgrade with high lumen output. Their competitive pricing and energy efficiency make them an excellent choice for retail sales. Additionally, their straightforward installation ensures ease of use for both you and your customers, making them a smart addition to your product offering.

Application

These bulbs are an excellent choice for any application requiring more light than a standard lightbulb can provide. Perfect for sheds, garages, workshops, work areas, storage facilities, and numerous other environments. They're designed to fit seamlessly into your existing light bulb sockets for instant upgrades.

Features

- Easy installation for quick upgrades.
- Energy efficient for reduced operating costs.
- Instant start with no warm-up time.
- 360-degree light spread provides complete coverage.

Options

- 12-24V or 120-277V.
- Choose from a variety of lumen outputs.

Mounting

- Screw-in E26 base for standard fixtures
- Screw-in E39 base for high-bay fixtures

Approved for use in Canada and USA, rated for use in dry or damp locations. Includes standard 3-year warranty—view our warranty policy for complete details.



3 YEAR
WARRANTY

Ordering Guide Example: CB060-8C50K078L-UNVNDNS-CSE26

Wattage	CRI	CCT	Lumens	Voltage	Driver	Enclosure Approval
100 100 watt 060 60 watt 030 30 watt 020 20 watt	8C 80	50K 5000K	130L 13,000 (100 Watt) 078L 7,800 (60 Watt) 039L 3,900 (30 Watt) 026L 2,600 (20 Watt)	UNV 120-277V (100,60 Watt) 347 347V (100 Watt) 122 12-24V (20,30 Watt)	ND Non-Dimmable DM Dimmable	ST Suitable in Fully Enclosed Fixture NS Non Suitable in Fully Enclosed Fixture

Lens	Base
CS Clear Smooth (60,100 Watt) FS Frosted Smooth (20,30 Watt)	E26 E26 Base (60,30,20 Watt) E39 E29 Base (100 Watt)

Specification Chart

Lumens	Watts	Color	CRI
13,000	100	5000K	80
7,800	60	5000K	80
3,900	30	5000K	80
2,600	20	5000K	80

Testing based on 25°C ambient temperature. Nominal calculations—actual outputs may vary based on product configurations. We reserve the right to correct printing errors or mistakes in our specifications.